



### Description

The 2-ply multi-purpose Tork Heavy-Duty Wiping Paper is ideal for mopping up liquids and hand drying. This paper can be used in either the Tork Floor or Wall Stand dispensers, which are developed for safety, efficiency and reliability or the Tork Maxi Centrefeed Dispenser, which is designed for smoother single-hand dispensing.

- Multipurpose - handles general wiping tasks that require strength and absorbency
- Its strong texture and high absorbency makes it ideal for removing oil, grease, lubricants and dirt
- High durability - stays strong even when wet, and is reusable
- QuickDry™
- Strong and absorbent
- Efficient
- Multipurpose

### Certifications




### Product Details

Number of Sheets	500
Roll width	23.5 cm
Roll diameter	26.2 cm
Embossing	Yes
Print	No
Sheet length	34 cm
Ply	2
Roll length	170 m
System	W1, W2
Color	White


### Shipping Data

	Consumer Units (CON)	Transport unit (TRP)	Pallet (PAL)
EAN	7322540183603	7322540183719	7322540747317
Packaging Material	none	Shrink	-
Pieces	1	2 (2 CON)	80 (40 TRP)
Height	235 mm	235 mm	1,336 mm
Length	262 mm	524 mm	1,200 mm
Width	262 mm	262 mm	1,000 mm
Gross Weight	1,678.95 g	3.42 kg	136.64 kg
Net Weight	1,637.95 g	3.28 kg	131.04 kg
Volume	16.13 dm3	32.26 dm3	1.29 m3
Layers Per Pallet	-	-	5
TRP Per Layer	-	-	8


## Compatible Products




**Tork Floor Stand Turquoise**  
652000



**Tork Floor Stand Red/Smoke**  
652008



**Tork Wall Stand Turquoise**  
652100



**Tork Wall Stand Red/Smoke**  
652108

## Environmental Information

Content	The product is made from  Fresh fibres The packaging material is made from paper or plastic.
Material	Fresh fibres Essity has an ambitious target that all raw materials derived from wood-based fresh fibre used in the production of our products is certified either in accordance with the FSC® or the Program for the Endorsement of Forest Certification (PEFC™). In addition, all wood-based fresh fibre shall fulfil the FSC® Controlled Wood standard, including third-party verification. The Essity Fibre Sourcing Policy describes this in more detail and can be found on <a href="http://www.essity.com">www.essity.com</a> . Fresh fibre pulp is produced from softwood or hardwood. The wood is subject to chemical and /or mechanical processes where the cellulose fibres are separated out and lignin and other residuals are removed. Bleaching is a cleaning process of the fibres and the aim is to achieve a bright pulp, but also to get a certain purity of the fibre in order to achieve the demands for hygiene products and in some cases to meet the requirements for food safety.
Chemicals	All chemicals (process aids as well as additives) are assessed from an environmental, occupational health and safety and product safety point of view. To control product performance we use additives: <ul> <li>Wet strength agents (for Wipers and Hand Towels)</li> <li>Dry strength agents (are used together with mechanical treatment of the pulp to make strong products like wipers)</li> <li>For coloured papers dyes and fixatives (to secure perfect fastness of the colour) are added</li> <li>For printing products printing inks (pigments with carriers and fixatives) are applied</li> <li>For multi ply products we often use water soluble glue to secure the integrity of the product</li> </ul> In most of our mills we do not add optical brighteners. We do not use softeners for professional hygiene products. High product quality is secured through quality and hygiene management systems throughout production, storage and transport. In order to maintain a stable process and product quality the paper manufacturing process is supported by the following chemicals/ process aids: <ul> <li>defoamers (surfactants and dispersing agents)</li> <li>pH-control (sodium hydroxide and sulphuric acid)</li> <li>retention aids (chemicals that help to agglomerate small fibres to prevent fibre loss)</li> <li>Coating chemicals (that help to control the creping of the paper to make it soft and absorbent)</li> </ul> To reuse broke we use: <ul> <li>Pulping aid (chemicals that help to repulp wet strong paper)</li> </ul> In the cleaning of our waste water we use flocculation agents and nutrients for the biological treatment to secure that no negative impact on water quality comes from our mills.
Food Contact	This product fulfills the legislative requirements for Food Contact materials, confirmed by external certification performed by a third party. The product is safe for wiping food contact surfaces and may also come occasionally into contact with foodstuffs for a short period of time.
Environmental certification	This product is certified with the EU Ecolabel with certificate number SE/004/001. This product is certified for FSC® with certificate number SA-COC-008266.
Packaging	Fulfilment of Packaging and Packaging Waste Directive (94/62/EC): Yes

Article creation date and latest article revision

Date of issue: 20-12-2019<br /> Revision date: 13-06-2025<br />

Production

This product is produced at Kostheim - DE mill and certified according to HACCP, ISO 9001, ISO 14001 (Environmental management systems), EMAS (eco-management and audit scheme), ISO 45001, ISO 50001 and FSC Chain-Of-Custody.

Disposal/destruction of used product

This product is used both for personal hygiene and for industrial processes. When used in industrial processes the product might through use be contaminated with different substances. This will determine how the used product will be handled / disposed of /destructed. The product itself is suitable for incineration. If used in industrial processes contact local authorities before destruction. When used for personal hygiene it can be collected together with household waste.

Essity UK Ltd, Southfields Road, Dunstable, Bedfordshire LU6 3EJ, United Kingdom