



Think ahead.

Tork Cleaning Cloth

510137



Description

- Excellent oil and water absorption, easily lifts grease and grime
- Compatible with most chemical solvents: Picks up and releases solvents more efficiently than textile products thereby reducing consumption
- Reusable, strong, durable wipe - excellent rental towel and rag replacement
- Aviation certification
- Professional use
- Versatile
- Scratch-free shine
- Efficient

Certifications



Product Details

Roll width	31.5 cm
Number of Sheets	400
Ply	1
Embossing	No
Print	No
Sheet length	38 cm
Roll diameter	25 cm
Roll length	152 m
System	W1, W2, W3
Color	White

Shipping Data

	Consumer Units (CON)	Transport unit (TRP)	Pallet (PAL)
EAN	7322540057263	7322540057270	7322540748369
Packaging Material	none	Carton	-
Pieces	1	1 (1 CON)	36 (36 TRP)
Height	333 mm	333 mm	1,160 mm
Length	264 mm	264 mm	1,200 mm
Width	264 mm	264 mm	1,000 mm
Gross Weight	2,938 g	2.94 kg	105.77 kg
Net Weight	2,633.4 g	2.63 kg	94.8 kg
Volume	23.21 dm3	23.21 dm3	0.84 m3
Layers Per Pallet	-	-	3
TRP Per Layer	-	-	12

Compatible Products



Environmental Information

Raw materials	Cellulose Pulp Polyester Polypropylene Functional agents or additives
Cellulose Pulp	Cellulose pulp is produced either from softwood or hardwood coming from responsibly managed forests. The wood chips are boiled together with chemicals to remove the lignin between the fibres. The pulp is TCF (Totally Chlorine Free) or ECF (Elementary Chlorine Free) bleached in order to achieve a clean, bright and strong product, but also to increase the hygienic and absorbent qualities.
Polyester	Polyester fibre is produced from terephthalic acid and ethylene glycol, which react through condensation to polyester resin. The molten resin is spun to fibres through spinnerets and cooled with air. The fibers are then cut to intended fiber length.
Polypropylene	Polypropylene or polypropene is a thermoplastic polymer made from oil. The moten resin is spun to endless fibres through spinnerets and cooled by air. The fibres form a web.
Functional agents and additives	Functional additives could be wet strength agent, antistatic agent and wetting additives /tensides.
Food Contact	This product fulfills the legislative requirements for Food Contact materials, confirmed by external certification performed by a third party. The product is safe for wiping food contact surfaces and may also come occasionally into contact with foodstuffs for a short period of time.
Environmental certification	This product is certified for FSC® with certificate number SA-COC-008266.
Packaging	Fulfilment of Packaging and Packaging Waste Directive (94/62/EC): Yes
Article creation date and latest article revision	Date of issue: 04-06-2021 Revision date: 23-05-2025
Production	This product is produced at Suameer - NL mill and certified according to ISO 9001 and ISO 14001 (Environmental management systems).
Disposal/destruction of used product	This product is mainly used for industrial processes. When used in industrial processes the product might through use be contaminated with different substances. This will determine how the used product will be handled/disposed of/destroyed. The product itself is suitable for incineration. If used in industrial processes contact local authorities before destruction.

Essity UK Ltd, Southfields Road, Dunstable, Bedfordshire LU6 3EJ, United Kingdom

